

# Attila 5230G

## Grey Acrylic Foam Tape

Created: 2012-09-20  
Updated: 2018-01-04

### GENERAL INFORMATION

---

Attila 5230G is a double sided high performance acrylic foam tape with a wide usage range for applications bonding high surface energy materials.


- 2,30mm thick
- Acrylic adhesive
- Temperature resistant up to 120°C
- UV-resistant

Attila 5230G can be die-cut for custom made parts and is available in all dimensions but standard widths are:

- 9mm x 16,5m
- 12mm x 16,5m
- 19mm x 16,5m
- 25mm x 16,5m

### CONSTRUCTION

---



### APPLICATIONS

---

Attila 5230G is used for many different kinds of permanent bonding applications and is suitable for both indoor and outdoor usage. Due to a high holding force power the tape can replace bonding solutions such as screws, rivets, nails and fluid adhesives. The Attila 5-series is suitable for bonding of high surface energy materials such as aluminium, glass, wood, concrete, and some plastics.

### USER GUIDELINES

---

To obtain optimal adhesion the surfaces must be clean and dry. Most frequent cleaning solvent is isopropyl/water (50:50 mixture) alcohol. Use safety instructions before using cleaners. Sometimes depending on surface a primer can be used to obtain a higher bonding force. Ideal temperature for tape application is between 21°C and 38°C. All Attila tapes require a dwell time of 72 hours for achieving 100% bonding strength.

## PRODUCT DATA

---

### Physical Data:

Adhesive:	Acrylic
Carrier:	-
Thickness:	Tape: 2,30mm Liner: 0,13mm Total: 2,43mm
Liner:	Red PE-film or white paper
Colour:	Grey
Shelf life*:	24 months
Storage:	Good storage conditions are in room temperature. Not recommended for direct exposure to sunlight or ultraviolet light.

\* From date of dispatch by ATC Tape Converting AB

### Performance Data:

Tensile strength:	1,90 Kg/cm
Elongation:	900 %
180° peel adhesion: (After 30 min)	≥2 Kg/cm
Dynamic shear adhesion: (After 30 min)	≥7,0 Kg/cm <sup>2</sup>
Heat resistance:	-30°C to +120°C

## CONTACT INFORMATION

---

### ATC Adhesive Tape Converting AB

Veddestavägen 17, Box 575  
175 26 Järfälla, SWEDEN

Telephone: +46 (0)8-564 708 80

Fax: +46 (0)8-564 708 89

E-mail: [info@atc.se](mailto:info@atc.se)

Web: [www.atc.se](http://www.atc.se)



**Intertek Intertek**